

Output Specifications:


MODEL NO.	OUTPUT RAIL	LOAD			VOLTAGE ACCURACY	RIPPLE NOISE	LINE REG.	LOAD REG.	EFFICIENCY TYPICAL
		MIN.	RATED	PEAK					
SNP-A037-M SNP-A037-M3	+12V	0A	2.5A	4A	+11.40V~+12.60V	100mVpp	±1%	±3%	82%
SNP-A038-M SNP-A038-M3	+15V	0A	2A	3A	+14.25V~+15.75V	100mVpp	±1%	±2%	83%
SNP-A039-M SNP-A039-M3	+24V	0A	1.3A	1.8A	+22.80V~+25.20V	200mVpp	±1%	±1%	86%

Note:


1. Output can provide up to peak load when the power supply starts up. Continuous staying in more than rated load is not allowed.
2. At factory, in 60% rated load condition, each output is checked to be within voltage accuracy.
3. Line regulation is defined by changing ±10% of input voltage from nominal line at rated load.
4. Load regulation is defined by changing ±40% of measured output load from 60% rated load.
5. Ripple & noise is measured by using 15MHz bandwidth limited oscilloscope and terminated each output with a 0.47uF capacitor at rated load and nominal line.
6. Hold up time is measured from the end of the last charging pulse to the time which the main output drops down to low limit of main output at rated load and nominal line.
7. Efficiency is measured at rated load, and nominal line.

Performance for SNP-A037-M:


1. Switching frequency ripple




2. Line frequency ripple




3. Output turn on wave form




4. Output turn off wave form



5. Hold-up time




6. +12V Over voltage protection




-Steven-

7. +12V step response




+12V step from 0.5A to 2.5A

8. Peak Load



9. FCC B



10. EN 55022 B

